

# GOOGO

ELITE TRAVELLER® 2



**PRIDE®**  
MOBILITY  
LIVE YOUR BEST®

Tel: +31 (0)85-0408630 . Fax: +31 (0)85-0430039  
pridemobility.eu . info@prideeurope.nl

De Go Go® Elite Traveller 2, een stabiele reisscooter, houdt moeiteloos jouw actieve levensstijl bij. Eenvoudige demontage, gemakkelijke opslag en veelzijdige mobiliteit maken hem tot de ideale dagelijkse scootmobiel.



8" massieve banden



compacte, opvouwbare stoel



Strak ontwerp

## Specificaties

Maximale belasting	136 kg
Snelheid	Tot 6,8 km/u
Maximale actieradius	Tot 22,1 km
Draaicirkel	3W: 790 mm 4W: 940 mm
Bodemvrijheid	3W: 32 mm 4W: 34 mm
Lengte	3W: 939 - 961 mm 4W: 1000 - 1036 mm
Breedte	494 mm
Banden	3W: 8" massief, voor en achter 4W: 7" massief voor, 8" massief achter
Aandrijving	Achterwielaandrijving, afgedichte transaxle, 24 volt gelijkstroommotor
Gewicht zonder accu's	3W: 35,3 kg 4W: 37,7 kg
Accu's	Type: Twee 12-volt, sealed lead-acid, non-spillable deep-cycle Capaciteit: 18 Ah
Meer?	Download het specificaties blad op de website

## Kenmerken

- Zero Turn-technologie
- Compacte, opvouwbare stoel
- Externe lader van 2 Amp
- 8" massieve banden
- Dankzij de vederlichte demontage en een draagvermogen van 136 kg zorgt hij voor een naadloze en efficiënte reiservaring.

1. Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire condition. This specification can be subject to a variance of (+ or -) 10%.
2. Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
3. Battery weight may vary based on battery manufacturer.
4. Includes standard seat weight.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

## Beschikbare kleuren

